

DERWENT- 2001-318995

ACC-NO:

DERWENT- 200562

WEEK:

COPYRIGHT 2006 DERWENT INFORMATION LTD

TITLE: Wheel structure for vehicles, comprises wheel and tire fitted on outer of wheel, which forms closed space having varied cross-sectional shapes in circumferential direction

INVENTOR: AKIYOSHI, Y; MORIYA, T ; YAMAUCHI, H ; AKIYOSHI, S ;
YAMAUCHI, Y

PATENT-ASSIGNEE: MITSUBISHI JIDOSHA KOGYO KK [MITM] , MITSUBISHI MOTOR CORP [MITM]

PRIORITY-DATA: 1999JP-0293658 (October 15, 1999) , 2005JP-0092538 (March 28, 2005) , 2005JP-0092539 (March 28, 2005)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE	PAGES	MAIN-IPC
JP 2005255162 A	September 22, 2005	N/A	009	B60B 021/12
EP 1092567 A2	April 18, 2001	E	011	B60C 019/00
JP 2001113902 A	April 24, 2001	N/A	005	B60B 021/12
US 20030197422 A1	October 23, 2003	N/A	000	B60B 019/00
US 6648421 B1	November 18, 2003	N/A	000	B60B 037/00
EP 1092567 B1	April 7, 2004	E	000	B60C 019/00
DE 60009626 E	May 13, 2004	N/A	000	B60C 019/00
US 6886616 B2	May 3, 2005	N/A	000	B60C 019/00
JP 2005200017 A	July 28, 2005	N/A	009	B60B 021/12
JP 3695255 B2	September 14, 2005	N/A	007	B60B 021/12

DESIGNATED-STATES: AL AT BE CH CY DE DK ES FI FR GB GR IE IT LI LT LU LV
MC MK NL PT RO SE SI DE FR

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO	APPL-DATE
JP2005255162A	Div ex	1999JP-0293658	October 15, 1999
JP2005255162A	N/A	2005JP-0092539	March 28, 2005
EP 1092567A2	N/A	2000EP-0120868	September 25, 2000
JP2001113902A	N/A	1999JP-0293658	October 15, 1999
US20030197422A1	Cont of	2000US-0688420	October 16, 2000
US20030197422A1	N/A	2003US-0442714	May 21, 2003
US 6648421B1	N/A	2000US-0688420	October 16, 2000
EP 1092567B1	N/A	2000EP-0120868	September 25, 2000
DE 60009626E	N/A	2000DE-0609626	September 25, 2000
DE 60009626E	N/A	2000EP-0120868	September 25, 2000
DE 60009626E	Based on	EP 1092567	N/A
US 6886616B2	Cont of	2000US-0688420	October 16, 2000
US 6886616B2	N/A	2003US-0442714	May 21, 2003
US 6886616B2	Cont of	US 6648421	N/A
JP2005200017A	Div ex	1999JP-0293658	October 15, 1999
JP2005200017A	N/A	2005JP-0092538	March 28, 2005
JP 3695255B2	N/A	1999JP-0293658	October 15, 1999
JP 3695255B2	Previous Publ.	JP2001113902	N/A

INT-CL (IPC): B60B019/00, B60B021/12 , B60B037/00 , B60C005/00 ,
B60C019/00 , F16F015/00

ABSTRACTED-PUB-NO: EP 1092567A

BASIC-ABSTRACT:

NOVELTY - A wheel structure comprises a wheel (10) and a tire fitted on a outer circumference of the wheel. A cross-sectional shape of a closed space (5) defined by the wheel and the tire is varied in a

circumferential direction so that a columnar resonance frequency in the space varies with a rotation of a wheel unit (12).

USE - As wheel structure for vehicles.

ADVANTAGE - The inventive wheel structure is capable of effectively reducing columnar resonance sound occurring in a wheel during a travel of a vehicle.

DESCRIPTION OF DRAWING(S) - The figures are perspective and schematic side views of the wheel structure.

Outer circumferential surface of rim 3

Closed space 5

Wheel 10

Wheel unit 12

Projections 15

**CHOSEN- Dwg.1,
DRAWING:**

**TITLE- WHEEL STRUCTURE VEHICLE COMPRISE WHEEL FIT OUTER WHEEL
TERMS: FORM CLOSE SPACE VARY CROSS SECTION SHAPE CIRCUMFERENCE
DIRECTION**

DERWENT-CLASS: A95 Q11 Q63

CPI-CODES: A12-T01;

**ENHANCED-POLYMER- Polymer Index [1.1] 018 ; H0124*R ; S9999
INDEXING: S1434**

Polymer Index [1.2] 018 ; ND01 ; Q9999
Q9256*R Q9212

SECONDARY-ACC-NO:

CPI Secondary Accession Numbers: C2001-098344

Non-CPI Secondary Accession Numbers: N2001-229297



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
18.04.2001 Bulletin 2001/16

(51) Int. Cl.⁷: **B60C 19/00**, **F16F 15/00**

(21) Application number: 00120868.5

(22) Date of filing: 25.09.2000

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 15.10.1999 JP 29365899

(71) Applicant:
Mitsubishi Jidosha Kogyo Kabushiki Kaisha
Tokyo 108-8410 (JP)

(72) Inventors:
• Akiyoshi, Yasuji,
Mitsubishi Jidosha Kogyo K. K.
Tokyo (JP)


- Moriya, Toshihiro,
Mitsubishi Jidosha Kogyo K. K.
Tokyo (JP)
- Yamauchi, Hiroshi,
Mitsubishi Jidosha Kogyo K. K.
Tokyo (JP)

(74) Representative:
Kern, Ralf M., Dipl.-Ing.
Ralf M. Kern & Partner
Postfach 14 03 29
80453 München (DE)

(54) Wheel structure

(57) A wheel structure for vehicles, capable of reducing a columnar resonance sound occurring in a wheel during a travel of a vehicle. A cross-sectional shape of a closed space 5 defined by a wheel 10 and a tire 1 is varied in the circumferential direction so that a columnar resonance frequency in the closed space 5 varies with a rotation of a wheel unit 12.

Fig. 10



Description**BACKGROUND OF THE INVENTION:****FIELD OF THE INVENTION:**

[0001] This invention relates to an improvement in a wheel structure for vehicles.

DESCRIPTION OF THE RELATED ART:

[0002] Fig. 10 is a schematic diagram of a wheel which has heretofore been used, and which will be described with reference to Fig. 10. It has heretofore been known that columnar resonance occurring in a closed space defined by a tire 1 and a wheel 10 causes the deterioration of a load noise during a travel of a vehicle. To be more exact, the columnar resonance is a resonance sound occurring when random vibration inputted from a road surface into the tire vibrates the air in the closed space 5 to cause a resonance phenomenon to occur in the vicinity of a columnar resonance frequency of the closed space 5.

[0003] This columnar resonance frequency is generally determined on the basis of an equation:

$$f=c/2\pi r$$

wherein (f) is a columnar resonance frequency, (c) a sound velocity, and (r) a distance between the center of a wheel and a radially intermediate portion 20 of the closed space but peaks of the columnar resonance frequency occur plurally in practice due to the deformation, which is ascribed to the weight of the vehicle, of a ground contacting surface of the tire. Anyway, a cross-sectional shape of the closed space 5 is constant at all times irrespective of the rotation of the wheel 12. Therefore, in a related art wheel structure, a value of the (r) of the above equation becomes constant. Accordingly, columnar resonance occurs with the same columnar resonance frequency at all times, and the resonance sound becomes offensive to the ear.

[0004] As a method of eliminating noise from a wheel, Japanese Patent Laid-Open No. 11704/1997 discloses techniques for reducing a noise of a wheel by providing a substantially cylindrical ring including a layer formed of at least one viscoelastic material on an outer circumferential surface of the wheel to thereby absorb mechanical vibration of the wheel. However, these techniques do not fundamentally hold down the occurrence of a columnar resonance sound, so that a satisfactory noise reducing effect cannot be obtained.

SUMMARY OF THE INVENTION:

[0005] The invention has been made in view of the above-mentioned circumstances, and provides a wheel structure for vehicles, capable of effectively reducing a

noise occurring due to a columnar resonance sound in a closed space in a wheel.

[0006] According to an aspect of the invention, the wheel structure has a wheel, and a tire fitted on an outer circumference of the wheel, a cross-sectional shape of a closed space defined by the wheel and tire being varied in a circumferential direction thereof so that a columnar resonance frequency of the closed space varies with a rotation of the wheel.

[0007] According to another aspect of the invention, projections are provided in parts of an inner side of the closed space, whereby a cross-sectional shape of the closed space varies in the circumferential direction thereof.

[0008] According to still another aspect of the invention, the projections are provided on an outer circumferential surface of a rim portion of the wheel.

[0009] According to a further aspect of the invention, the projections are provided on an inner circumferential surface of a tread of the tire.

[0010] According to another aspect of the invention, the projections are provided on inner circumferential surfaces of side walls of the tire.

[0011] According to still another aspect of the invention, a length of each of the projections 15 is substantially 1/4 of a circumferential length of the tire, two projections being provided in a circumferentially equally spaced manner.

[0012] According to a further aspect of the invention, a ratio of a cross-sectional area of each of the projections to that of the closed space which is not provided with the projection is set substantially not smaller than 2.5%.

[0013] According to another aspect of the invention, a circumferentially irregularly surfaced belt is fitted on an outer circumferential surface of the rim portion of the wheel to thereby circumferentially vary a cross-sectional shape of the closed space.

[0014] According to still another aspect of the invention, the outer circumferential surface of the rim portion of the wheel is formed irregularly in the circumferential direction to thereby circumferentially vary a cross-sectional shape of the closed space.

[0015] According to a further aspect of the invention, the closed space is formed so that a ratio of a length of a radially longest portion thereof to that of a radially shortest portion thereof becomes substantially not larger than 97%.

BRIEF DESCRIPTION OF THE DRAWINGS:

[0016] Preferred embodiments of the invention will be described in detail on the basis of the following figures, wherein:

Fig. 1 is a perspective view of wheel in a first mode of embodiment of the invention;

Fig. 2 is a schematic side view illustrating the oper-

ation of the wheel in the first mode of embodiment of the invention;

Fig. 3 is a schematic side view illustrating the operation of the wheel in the first mode of embodiment of the invention;

Fig. 4 is a diagram comparatively showing noise level characteristics with respect to a columnar resonance frequency in the first mode of embodiment of the invention and those of a related art wheel;

Fig. 5 is a diagram comparatively showing noise level characteristics with respect to a resonance frequency of the wheel in the first mode of embodiment of the invention and those of a related art wheel;

Fig. 6 is a perspective view of a wheel in a second mode of embodiment of the invention;

Fig. 7 is a schematic side view of a wheel in a third mode of embodiment of the invention;

Fig. 8 is a schematic side view a wheel in a fourth mode of embodiment of the invention;

Fig. 9 is a schematic view of a wheel in another mode of embodiment of the invention, wherein:

Fig. 9A is a side view; and

Fig. 9B is a schematic view showing a cross section taken along the arrow-carrying line K-K in Fig. 9A; and

Fig. 10 is a schematic side view of a related art wheel.

DESCRIPTION OF THE PREFERRED EMBODIMENTS:

[0017] Modes of embodiment of the invention will now be described with reference to the drawings. Figs. 1-5 show a first mode of embodiment of the wheel structure for vehicles according to the present invention, Fig. 6 a second mode of embodiment of the wheel structure for vehicles according to the present invention, Fig. 7 a third mode of embodiment of the wheel structure for vehicles according to the present invention, Fig. 8 a fourth mode of embodiment of the wheel structure for vehicles according to the present invention; and Fig. 9 another mode of embodiment of the wheel structure for vehicles according to the present invention. Referring to Figs. 1-9, structural parts identical with those of the above-described related art wheel structure will be designated by the same reference numerals.

[0018] First, a first mode of embodiment of the wheel structure for vehicles according to the present invention will be described. As shown in Fig. 1, four side elevationally arcuate bulkheads (projections) 15 each of which has a length of about 1/8 of that of the whole of an outer circumferential surface 3 of a rim portion 6 of a wheel 10 of a vehicle are arranged at regular intervals on the same outer circumferential surface 3, whereby a cross-sectional shape of a closed space 5 enclosed with and defined by a tire 1 and a wheel 10, which constitute a wheel unit 12, is varied in the circumferential

direction thereof as shown in Fig. 3.

[0019] The first mode of embodiment of the wheel structure for vehicles according to the present invention is formed as described above. Accordingly, a columnar resonance frequency in the closed space in a condition A in which a bulkhead 15 does not exist as shown in Fig. 2 on the part of the outer circumferential surface 3 of the rim portion 6 which is opposed to a ground contacting surface 17 of the tire and that of the closed space in a condition B attained after the wheel unit in the condition A makes a substantially 1/8 turn to have a bulkhead 15 positioned on the above-mentioned part of the outer circumferential surface 3 are different. Referring to Figs. 2 and 3, a reference numeral 20 denotes a radially intermediate portion of the closed space 5.

[0020] To be more exact, when the part of the outer surface of the tire which is just under the part of the rim portion 6 which has a bulkhead 15 contacts a ground surface, a distance H_B between the portion of an inner circumferential surface 8 of the tire which corresponds to the ground contacting surface 17 of the tire and the portion of the outer circumferential surface 3 (a surface 27 of the bulkhead 15) of the wheel 10 becomes shorter by a level corresponding to the height of the bulkhead 15 than that H_A between the mentioned parts in a case (condition A) where the part of the outer surface of the tire which is just under the part of the rim portion which does not have a bulkhead 15 contacts the ground surface. Therefore, the radially intermediate portion 20 of the closed space 5 is displaced toward the side of the outer circumferential surface of the wheel unit 12.

[0021] Accordingly, in the condition A, and B, the height in cross section of the ground contacting portion of the closed space 5 is different. Also, the position of the part of the radially intermediate portion 20 of the closed space which corresponds to the ground contacting portion of the tire is different. Since the columnar resonance frequency is determined in accordance with a distance (r) between the center of a wheel unit and a radially intermediate portion 20 thereof as mentioned above, the columnar resonance frequencies in the respective condition become different. The columnar resonance frequency is varied continuously with the rotation of the wheel unit 12 between the levels a, a' (refer to a solid line designated by the word "Embodiment") in the condition A and levels b, b' (refer to a broken line designated by the word "Embodiment") in the condition B as shown in Fig. 4.

[0022] Consequently, in a related art wheel structure in which a columnar resonance frequency in a closed space 5 is constant irrespective of a rotation of a wheel unit 12, resonance (refer to a one-dot chain line designated by words "Related art example") occurs with the same frequency at all times even when the wheel unit 12 is rotated. On the other hand, in the above-described mode of embodiment of the wheel structure, the columnar resonance frequency varies cyclically in every 1/4 turn of the wheel unit 12, so that the length of

the time during which resonance occurs with a single frequency decreases. Therefore, as shown by the solid line and broken line in Fig. 4, a noise level relative to a columnar resonance frequency becomes low. Moreover, since the columnar resonance frequency has various levels, a sound pressure level decreases, and this enables a driver to rarely feel noise.

[0023] When a noise level of columnar resonance lowers, an amplitude by vibration in a region of columnar resonance frequency transmitted to the wheel 10 also lowers, so that noise occurring due to the resonance of the wheel 10 ascribed to the columnar resonance can also be reduced.

[0024] The wheel 10 has characteristic frequencies of two modes, i.e. a bell mode in which both end portions in the longitudinal direction of a vehicle of the wheel 10 are displaced around a spindle in the opposite directions with respect to the widthwise direction of the vehicle, and resonate, and a bending mode in which the mentioned portions of the wheel are displaced around the spindle in the same direction with respect to the widthwise direction of the vehicle, and resonate. When these two characteristic frequencies exist in a frequency region in the vicinity of a columnar resonance frequency the amplitude of which is still larger than those of other frequencies out of the frequencies inputted into the wheel 10, the resonance of the wheel 10 is amplified, and this would render it unable to reduce the noise level effectively.

[0025] However, the characteristic frequency in the above-mentioned bending mode is proportional to a bending rigidity of the wheel 10, and that in the bell mode in inverse proportion to the weight of the wheel 10. Therefore, when the above-mentioned bulkheads 15 are provided on the outer circumferential surface 3, the bending rigidity of the wheel 10 is improved with the characteristic frequency in the bending mode increasing accordingly, the weight of the wheel 10 increasing with the characteristic frequency in the bell mode decreasing accordingly. Therefore, as shown by a solid line in Fig. 5, even when the characteristic frequencies of the wheel 10 are in the columnar resonance frequency region, the two characteristics can be removed from the columnar resonance frequency region by regulating the thickness of, a material for, and the weight of the bulkheads 15. This can prevent the amplification (refer to a one-dot chain line in Fig. 5) of resonance of the wheel 10 which readily occurs in a related art wheel structure.

[0026] A second mode of embodiment of the wheel structure for vehicles according to the invention will now be described. As shown in Fig. 6, in this wheel structure, a band 30 is wound around an outer circumferential surface 3 of a rim portion 6 of a wheel 10. This band 30 is provided with fastener portions 28 at both ends thereof, and has a continuous irregular shape in side elevation. The band is wound around the outer circumferential surface 3 of the rim portion 6 of the wheel 10, and fixed by combining with each other the fastener portions 28 at

both ends thereof. Owing to this band 30, a cross-sectional shape of a closed space 28 is varied in the circumferential direction.

[0027] Since the second mode of embodiment of the wheel structure for vehicles according to the invention is formed as described above, it is possible not only to effectively obtain a noise reducing effect substantially identical with that obtained in the above-described mode of embodiment but also to simplify the manufacturing step and carry out an after-band-fixing-operation.

[0028] A third mode of embodiment of the wheel structure for vehicles according to the invention will now be described.

[0029] As shown in Fig. 7, an outer circumferential surface 3 of a rim portion 6 of a wheel 10 in this wheel structure is formed to a shape other than a true circular shape.

[0030] The third mode of embodiment of the wheel structure according to the invention is formed in this manner so as to vary a cross-sectional shape of a closed space 5 in the circumferential direction. Accordingly, a noise reducing effect substantially identical with that of each of the above-described modes of embodiment is obtained.

[0031] A fourth mode of embodiment of the wheel structure for vehicles according to the invention will now be described. As shown in Fig. 8, bulkheads 15' in this wheel structure are provided on parts of inner circumferential surface of a tire, whereby a cross-sectional shape of a closed space 5 is varied in the circumferential direction.

[0032] The fourth mode of embodiment of the wheel structure according to the invention is formed in this manner so as to vary a cross-sectional shape of the closed space 5 in the circumferential direction. Accordingly, a noise reducing effect substantially identical with that in each of the above-described modes of embodiment is obtained.

[0033] In the above-described modes of embodiment, noise is reduced by forming the closed space so that the distance (r) (length of the radially intermediate line in the closed space 5) between the center of the wheel and the radially intermediate portion 20 of the closed space 5 varies with the rotation of the wheel unit 12 to thereby produce an effect in varying the columnar resonance frequency in the closed space 5 during the rotation of the wheel unit 12. Owing to the study made by the developers of the present invention, it has become clear that, even when the cross-sectional shape of the closed space 5 is varied so that the cross-sectional area of the closed space varies with the rotation of the wheel unit 12, the columnar resonance frequency in the closed space 5 can be varied by the rotation of the wheel unit 12.

[0034] For example, when bulkheads 15" are provided on inner surfaces of side portions of a tire with respect to the widthwise direction of the tire as shown in Figs. 9A and 9B, the cross-sectional area of the portion

of the closed space 5 which corresponds to the ground contacting surface 17 of the tire in the condition in which a bulkhead 15" exists in the mentioned portion and that of the same portion of the closed space 5 in the condition in which a bulkhead 15" does not exist in the same portion differ from each other. Therefore, noise can be reduced by varying the columnar resonance frequency by the rotation of the wheel unit 12 in the same manner as in the above-described modes of embodiment.

[0035] These modes of embodiment are formed by arranging four or two bulkheads 15, 15' and 15". When the wheel structure is formed by arranging two bulkheads, each of which has a length substantially 1/4 of the whole circumferential length of the outer circumferential surface 3 of the rim portion 6 of the wheel 10, on the inner surface of a tire or on the mentioned outer circumferential surface 3 at regular intervals, the time during which resonance occurs with a single columnar resonance frequency can be reduced most, and noise can also be lowered to the greatest extent.

[0036] When a distance of the radially shortest portion of the closed space 5 which is other than the portion thereof which corresponds to the ground contacting surface 17 of a tire is set to not larger than 97% (or substantially not larger than 97%), or, when the cross-sectional area of a bulkhead 15 is set to not smaller than 2.5% (or substantially not smaller than 2.5%) with respect to that of the portion of the closed space 5 which is not provided with a bulkhead, the columnar resonance frequency can be staggered effectively, and a larger noise reducing effect is obtained.

[0037] In the wheel structure for vehicles according to the present invention described above, the time during which resonance occurs with a single columnar resonance frequency can be reduced, and a level of noise occurring due to columnar resonance can be lowered.

Claims

1. A wheel structure comprising:
 - a wheel 10, and
 - a tire 1 fitted on an outer circumference of the wheel 10,
 - a cross-sectional shape of a closed space 5 defined by the wheel 10 and tire 1 being varied in a circumferential direction thereof so that a columnar resonance frequency in the closed space 5 varies with a rotation of a wheel unit 12.
2. A wheel structure according to Claim 1, wherein projections 15 are provided on parts of an inner side of the closed space 5, whereby a cross-sectional shape of the closed space 5 is varied in the circumferential direction thereof.
3. A wheel structure according to Claim 2, wherein the

projections 15 are provided on an outer circumferential surface 3 of a rim portion of the wheel 10.

4. A wheel structure according to Claim 2, wherein the projections 15 are provided on an inner circumferential surface 8 of a tread of the tire 1.
5. A wheel structure according to Claim 2, wherein the projections are provided on inner circumferential surfaces 8 of side walls of the tire 1.
6. A wheel structure according to Claim 2, wherein a length of each of the projections 15 is substantially 1/4 of a circumferential length of the tire 1, two projections 15 being provided in a circumferentially equally spaced manner.
7. A wheel structure according to Claim 2, wherein a ratio of a cross-sectional area of each of the projections 15 to that of the portion of the closed space 5 which is not provided with the projection 15 is set to substantially not lower than 2.5%.
8. A wheel structure according to Claim 1, wherein a circumferentially irregularly surfaced band 30 is fitted on an outer circumferential surface 3 of the rim portion of the wheel 1 to thereby circumferentially vary a cross-sectional shape of the closed space 5.
9. A wheel structure according to Claim 1, wherein the outer circumferential surface 3 of the rim portion of the wheel 1 is formed irregularly in the circumferential direction to thereby circumferentially vary a cross-sectional shape of the closed space 5.
10. A wheel structure according to Claim 1, wherein the closed space 5 is formed so that a ratio of a length of a radially longest portion thereof to that of a radially shortest portion thereof becomes substantially not larger than 97%.

Fig. 1




Fig. 2

condition A




Fig. 3 condition B




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10

